

光顯示器專用恆溫恆濕機-FPD THS
FPD Programmable Temperature Humidity Chamber




Advanced Technology. Key Value. Convenience Safe... 科技創新技術.核心價值.即時安全設計...

規格表(Specification Table):

規格(Specification)	FPD-THS-A
溫度與濕度控制(Temperature And Humidity Control)	
內箱尺寸(Inside Dimensions (W*D*H)cm)	125×80×100
外箱尺寸(Outside Dimensions (W*D*H)cm)	198×122×195
觀測試窗尺寸(W.H)cm)	80W×80H cm
動態/靜態發熱負載	1500W (50℃/80 %)/100KG
內容積(Inside Capacity)公升(Liter)	1000L
重量(Weight)(Approx.)(kg)	
絕緣材料(Insulation Material)	防火PU發泡(70℃~100℃)或玻璃纖維+防火 PU發泡(110℃以上)
內箱材料(Internal Material)	SUS#304不鏽鋼
外箱材料(External Material)	(Stainless Steel)+9493 粉體塗裝(3B Surface Treatment)
升溫時間(Heating Time(20℃→H.T.)min)	100℃ / 30 min
降溫時間(Cooling time(20℃→L.T.)min)	(-30℃ / 50 min) / (-40℃ / 70 min)
濕度範圍(Humidity range)	20~95%R.H
溫度分布偏差(Temperature Variation ℃)	±1.5℃ (空載)
中心點濕度分布均勻度 (Humidity Variation %R.H)	±5% (空載)
溫度穩定度(Temperature Stability ℃)	±0.2
濕度穩定度(Humidity Stability %R.H)	±2
溫度解析度(Temperature Resolution℃)	0.01
濕度解析度(Humidity Resolution %R.H)	0.1
出風方式	側吹
主要裝置(Major Device)	
循環系統(Circulation)	機械式的對流系統(Mechanical Convection System)
冷凍系統(Cooling System)	水冷式冷卻密閉型/半密閉型壓縮機(Water Cooling Hermetic/semi-hermetic Compressor) HFC環保冷媒Cascade / Single Stage
加熱系統(Heating System)	平衡濕度(Balance Humidity)P.I.D.+P. W.M.+S.S.R.
加濕系統(Humidity System)	平衡溫度(Balance Temperature)P.I.D.+P. W.M.+S.S.R.
加濕給水系統(Humidification Water Supply)	自動水位控制(Automatic Water Regulation)+RO逆滲透給水系統
控制器(Controller)	PC Based Touch Panel
電源(Power Source)	AC 220V / 3 ϕ AC 380V / 3 ϕ
水質(Water Quality)	蒸餾水(Disstilled Water Only)
環境溫度(Environmental Temperature)	+5℃~+30℃
地板空間(Floor space(W * D)cm)	220×240
擴充設備	時序插座(Power Supply Socket),e化管理系統(e Manage System)10公分測試孔

※以上規格，請以實體報價為主 (For Above Accessories, Their Actual Specifications May Vary)

Model Code



溫濕度可控制能力範圍表(Temperature&Humidity Range)

